

# Интегрированные машины Linus

## Технические характеристики

По вопросам продаж и поддержки обращайтесь:

Алматы (727)345-47-04  
Ангарск (3955)60-70-56  
Архангельск (8182)63-90-72  
Астрахань (8512)99-46-04  
Барнаул (3852)73-04-60  
Белгород (4722)40-23-64  
Благовещенск (4162)22-76-07  
Брянск (4832)59-03-52  
Владивосток (423)249-28-31  
Владикавказ (8672)28-90-48  
Владимир (4922)49-43-18  
Волгоград (844)278-03-48  
Вологда (8172)26-41-59  
Воронеж (473)204-51-73  
Екатеринбург (343)384-55-89

Иваново (4932)77-34-06  
Ижевск (3412)26-03-58  
Иркутск (395)279-98-46  
Казань (843)206-01-48  
Калининград (4012)72-03-81  
Калуга (4842)92-23-67  
Кемерово (3842)65-04-62  
Киров (8332)68-02-04  
Коломна (4966)23-41-49  
Кострома (4942)77-07-48  
Краснодар (861)203-40-90  
Красноярск (391)204-63-61  
Курск (4712)77-13-04  
Курган (3522)50-90-47  
Липецк (4742)52-20-81

Магнитогорск (3519)55-03-13  
Москва (495)268-04-70  
Мурманск (8152)59-64-93  
Набережные Челны (8552)20-53-41  
Нижний Новгород (831)429-08-12  
Новокузнецк (3843)20-46-81  
Ноябрьск (3496)41-32-12  
Новосибирск (383)227-86-73  
Омск (3812)21-46-40  
Орел (4862)44-53-42  
Оренбург (3532)37-68-04  
Пенза (8412)22-31-16  
Петрозаводск (8142)55-98-37  
Псков (8112)59-10-37  
Пермь (342)205-81-47

Ростов-на-Дону (863)308-18-15  
Рязань (4912)46-61-64  
Самара (846)206-03-16  
Санкт-Петербург (812)309-46-40  
Саратов (845)249-38-78  
Севастополь (8692)22-31-93  
Саранск (8342)22-96-24  
Симферополь (3652)67-13-56  
Смоленск (4812)29-41-54  
Сочи (862)225-72-31  
Ставрополь (8652)20-65-13  
Сургут (3462)77-98-35  
Сыктывкар (8212)25-95-17  
Тамбов (4752)50-40-97  
Тверь (4822)63-31-35

Тольятти (8482)63-91-07  
Томск (3822)98-41-53  
Тула (4872)33-79-87  
Тюмень (3452)66-21-18  
Ульяновск (8422)24-23-59  
Улан-Удэ (3012)59-97-51  
Уфа (347)229-48-12  
Хабаровск (4212)92-98-04  
Чебоксары (8352)28-53-07  
Челябинск (351)202-03-61  
Череповец (8202)49-02-64  
Чита (3022)38-34-83  
Якутск (4112)23-90-97  
Ярославль (4852)69-52-93

**Россия** +7(495)268-04-70

**Казахстан** +7(727)345-47-04

**Беларусь** +(375)257-127-884

**Узбекистан** +998(71)205-18-59

**Киргизия** +996(312)96-26-47

эл.почта: [cie@nt-rt.ru](mailto:cie@nt-rt.ru) || сайт: <https://celli.nt-rt.ru/>



# Linus

Linus is an integrated overcounter refrigeration unit, available in 40, 60, 80 and 120 models with different performance levels. Depending on the model, Linus can dispense up to 21, 27, 40 or 46 litres per hour in continuous operation.



## KEY STRENGTHS



### Performance

Linus is an integrated overcounter refrigeration unit equipped with taps for direct product dispensing. The technology used is a dry ice bank, with Linus featuring an aluminium block in which the evaporator and product coils are embedded. The advantage of the dry technology is the extremely fast startup (just a few minutes to reach the appropriate temperature) and the absence of liquids to add or remove.

Linus is available in 40, 60, 80 and 120 models with different performance levels. Depending on the model, Linus can dispense up to 21, 27, 40 or 46 litres per hour in continuous operation.



### Advanced Features

Linus can also be installed undercounter and connected to pipes that bring the product to an overhead counter, functioning as a small fixed station with dry technology. It is available in two versions:

RTU Version: Linus is also available with an integrated pressure reducer in the body and a beer hose for connection to an external beer keg.

C/A Version: Linus is also available with an integrated air compressor, suitable for use with keykegs.



### Serviceability

The absence of liquid in the refrigeration circuit means that no filling is required before installation, and no draining or cleaning is required during installation.



### Convenience

The transport of an integrated dry technology machine allows it to be used in mobile or inclined environments (e.g. food trucks), where vibrations could cause liquid spillage. The fast start-up time reduces downtime for any business.



### Design & User Experience

Linus is available with 1 tap (model 40) or with 1 or 2 taps for the larger models. The choice of tap is between Celli BT and Celli FC4 CFR. The body of Linus is made entirely of 430 stainless steel with a polished finish for medium to high resistance to spilt liquids or water used for cleaning. The drip tray, included as standard, is useful for collecting spilt liquids.



### Hygien & Safety

The absence of liquids, and therefore the potential accumulation of microorganisms inside the body, ensures greater hygiene and safety.



## LINUS VERSIONS

# LINUS 40

### Type of beverages



Beer



Wine

### Refrigerant gas

R290

### Finishing



Steel

### Cooling method



AIR

### Lines



1-2



40-50 place settings



feet only



| Linus 40                                                   |           |                       |
|------------------------------------------------------------|-----------|-----------------------|
| General data sheet                                         |           |                       |
| Water basin (net)                                          | L         | dry block (aluminium) |
| Ice bank                                                   | kg        |                       |
| Compressor's nominal power                                 | CV        | 1/7                   |
| Standard agitator pump                                     | m         |                       |
| Performance & Consumption                                  |           |                       |
| Performance - Cooling power                                | W         | 433                   |
| Performance - hourly peak - $\Delta T20^{\circ}\text{C}$   | L/h       |                       |
| Performance - daily average - $\Delta T20^{\circ}\text{C}$ | L/h       | 21                    |
| Max power absorption                                       | W         | 260                   |
| Average daily consumption - standby **                     | kWh       |                       |
| Average daily consumption**                                | kWh       |                       |
| Overall Height (with pump)*                                | cm        | 39                    |
| Length x Width                                             | cm x cm   | 38 x 31               |
| Net Empty Weight                                           | kg        | 25                    |
| Coils - max number 15/20 m each***                         | n°        | -                     |
| Coils - max number including 10 m coils**                  | n°        | 1                     |
| Available Versions                                         |           |                       |
| Electric supply                                            |           | 220-240V AC 50/60 Hz  |
| Plug to choose                                             |           | Schuko                |
| Options to chose                                           |           |                       |
| Number of coils                                            | n°        | 1                     |
| Coils inlet/outlet                                         |           | n/a                   |
| Coils diameter                                             | mm x mm   | 7x8 10x11             |
| Thermostat option                                          |           | mechanical only       |
| Enhanced pump                                              | steps / m | n/a                   |

This is a all-comprehensive list fo all possible features, that are already technically feasible. Not all the combinations of these features (not each configuration) is already present in stock and in the price list. Reference can be found in the Celli price list.



LINUS

Each item number includes coils, pump, plug/V

## LINUS VERSIONS

# LINUS 60

### Type of beverages



Beer



Wine

### Refrigerant gas

R290

### Finishing



Steel

### Cooling method



AIR

### Lines



1-2



50-60 place  
settings



feet only



### Linus 60

#### General data sheet

|                            |    |                       |
|----------------------------|----|-----------------------|
| Water basin (net)          | L  | dry block (aluminium) |
| Ice bank                   | kg |                       |
| Compressor's nominal power | CV | 1/4                   |
| Standard agitator pump     | m  |                       |

#### Performance & Consumption

|                                                            |         |         |
|------------------------------------------------------------|---------|---------|
| Performance - Cooling power                                | W       | 630     |
| Performance - hourly peak - $\Delta T20^{\circ}\text{C}$   | L/h     |         |
| Performance - daily average - $\Delta T20^{\circ}\text{C}$ | L/h     | 27      |
| Max power absorption                                       | W       | 350     |
| Average daily consumption - standby **                     | kWh     |         |
| Average daily consumption**                                | kWh     |         |
| Overall Height (with pump)*                                | cm      | 44      |
| Length x Width                                             | cm x cm | 43 x 32 |
| Net Empty Weight                                           | kg      | 38      |
| Coils - max number 15/20 m each***                         | n°      | -       |
| Coils - max number including 10 m coils**                  | n°      | 2       |

#### Available Versions

|                 |  |                      |
|-----------------|--|----------------------|
| Electric supply |  | 220-240V AC 50/60 Hz |
| Plug to choose  |  | Schuko               |

#### Options to chose

|                    |           |                 |
|--------------------|-----------|-----------------|
| Number of coils    | n°        | 1; 2            |
| Coils inlet/outlet |           | n/a             |
| Coils diameter     | mm x mm   | 7x8 10x11       |
| Thermostat option  |           | mechanical only |
| Enhanced pump      | steps / m | n/a             |

This is a all-comprehensive list fo all possible features, that are already technically feasible. Not all the combinations of these features (not each configuration) is already present in stock and in the price list. Reference can be found in the Celli price list.



LINUS

Each item number includes coils, pump, plug/V

## LINUS VERSIONS

# LINUS 80

### Type of beverages



Beer



Wine

### Refrigerant gas

R290

### Finishing



Steel

### Cooling method



AIR

### Lines



1-2



80-90 place settings



feet only



| Linus 80                                                   |           |                       |
|------------------------------------------------------------|-----------|-----------------------|
| General data sheet                                         |           |                       |
| Water basin (net)                                          | L         | dry block (aluminium) |
| Ice bank                                                   | kg        |                       |
| Compressor's nominal power                                 | CV        | 3/8                   |
| Standard agitator pump                                     | m         |                       |
| Performance & Consumption                                  |           |                       |
| Performance - Cooling power                                | W         | 931                   |
| Performance - hourly peak - $\Delta T20^{\circ}\text{C}$   | L/h       |                       |
| Performance - daily average - $\Delta T20^{\circ}\text{C}$ | L/h       | 40                    |
| Max power absorption                                       | W         | 620                   |
| Average daily consumption - standby **                     | kWh       |                       |
| Average daily consumption**                                | kWh       |                       |
| Overall Height (with pump)*                                | cm        | 43                    |
| Length x Width                                             | cm x cm   | 58 x 38               |
| Net Empty Weight                                           | kg        | 42                    |
| Coils - max number 15/20 m each***                         | n°        | -                     |
| Coils - max number including 10 m coils**                  | n°        | 2                     |
| Available Versions                                         |           |                       |
| Electric supply                                            |           | 220-240V AC 50/60 Hz  |
| Plug to choose                                             |           | Schuko                |
| Options to chose                                           |           |                       |
| Number of coils                                            | n°        | 1; 2                  |
| Coils inlet/outlet                                         |           | n/a                   |
| Coils diameter                                             | mm x mm   | 7x8 10x11             |
| Thermostat option                                          |           | mechanical only       |
| Enhanced pump                                              | steps / m | n/a                   |

This is a all-comprehensive list fo all possible features, that are already technically feasible. Not all the combinations of these features (not each configuration) is already present in stock and in the price list. Reference can be found in the Celli price list.



LINUS

Each item number includes coils, pump, plug/V

## LINUS VERSIONS

# LINUS 120

### Type of beverages



Beer



Wine

### Refrigerant gas

R290

### Finishing



Steel

### Cooling method



AIR

### Lines



1-2



90-100 place  
settings



feet only



| Linus 120                                                  |           |                       |
|------------------------------------------------------------|-----------|-----------------------|
| General data sheet                                         |           |                       |
| Water basin (net)                                          | L         | dry block (aluminium) |
| Ice bank                                                   | kg        |                       |
| Compressor's nominal power                                 | CV        | 1/2                   |
| Standard agitator pump                                     | m         |                       |
| Performance & Consumption                                  |           |                       |
| Performance - Cooling power                                | W         | 1.141                 |
| Performance - hourly peak - $\Delta T20^{\circ}\text{C}$   | L/h       |                       |
| Performance - daily average - $\Delta T20^{\circ}\text{C}$ | L/h       | 46                    |
| Max power absorption                                       | W         | 680                   |
| Average daily consumption - standby **                     | kWh       |                       |
| Average daily consumption**                                | kWh       |                       |
| Overall Height (with pump)*                                | cm        | 43                    |
| Length x Width                                             | cm x cm   | 58 x 38               |
| Net Empty Weight                                           | kg        | 45                    |
| Coils - max number 15/20 m each***                         | n°        | -                     |
| Coils - max number including 10 m coils**                  | n°        | 2                     |
| Available Versions                                         |           |                       |
| Electric supply                                            |           | 220-240V AC 50/60 Hz  |
| Plug to choose                                             |           | Schuko                |
| Options to chose                                           |           |                       |
| Number of coils                                            | n°        | 1; 2                  |
| Coils inlet/outlet                                         |           | n/a                   |
| Coils diameter                                             | mm x mm   | 7x8 10x11             |
| Thermostat option                                          |           | mechanical only       |
| Enhanced pump                                              | steps / m | n/a                   |

This is a all-comprehensive list fo all possible features, that are already technically feasible. Not all the combinations of these features (not each configuration) is already present in stock and in the price list. Reference can be found in the Celli price list.



LINUS

Each item number includes coils, pump, plug/V

Алматы (727)345-47-04  
Ангарск (3955)60-70-56  
Архангельск (8182)63-90-72  
Астрахань (8512)99-46-04  
Барнаул (3852)73-04-60  
Белгород (4722)40-23-64  
Благовещенск (4162)22-76-07  
Брянск (4832)59-03-52  
Владивосток (423)249-28-31  
Владикавказ (8672)28-90-48  
Владимир (4922)49-43-18  
Волгоград (844)278-03-48  
Вологда (8172)26-41-59  
Воронеж (473)204-51-73  
Екатеринбург (343)384-55-89

Иваново (4932)77-34-06  
Ижевск (3412)26-03-58  
Иркутск (395)279-98-46  
Казань (843)206-01-48  
Калининград (4012)72-03-81  
Калуга (4842)92-23-67  
Кемерово (3842)65-04-62  
Киров (8332)68-02-04  
Коломна (4966)23-41-49  
Кострома (4942)77-07-48  
Краснодар (861)203-40-90  
Красноярск (391)204-63-61  
Курск (4712)77-13-04  
Курган (3522)50-90-47  
Липецк (4742)52-20-81

Магнитогорск (3519)55-03-13  
Москва (495)268-04-70  
Мурманск (8152)59-64-93  
Набережные Челны (8552)20-53-41  
Нижний Новгород (831)429-08-12  
Новокузнецк (3843)20-46-81  
Ноябрьск (3496)41-32-12  
Новосибирск (383)227-86-73  
Омск (3812)21-46-40  
Орел (4862)44-53-42  
Оренбург (3532)37-68-04  
Пенза (8412)22-31-16  
Петрозаводск (8142)55-98-37  
Псков (8112)59-10-37  
Пермь (342)205-81-47

Ростов-на-Дону (863)308-18-15  
Рязань (4912)46-61-64  
Самара (846)206-03-16  
Санкт-Петербург (812)309-46-40  
Саратов (845)249-38-78  
Севастополь (8692)22-31-93  
Саранск (8342)22-96-24  
Симферополь (3652)67-13-56  
Смоленск (4812)29-41-54  
Сочи (862)225-72-31  
Ставрополь (8652)20-65-13  
Сургут (3462)77-98-35  
Сыктывкар (8212)25-95-17  
Тамбов (4752)50-40-97  
Тверь (4822)63-31-35

Тольятти (8482)63-91-07  
Томск (3822)98-41-53  
Тула (4872)33-79-87  
Тюмень (3452)66-21-18  
Ульяновск (8422)24-23-59  
Улан-Удэ (3012)59-97-51  
Уфа (347)229-48-12  
Хабаровск (4212)92-98-04  
Чебоксары (8352)28-53-07  
Челябинск (351)202-03-61  
Череповец (8202)49-02-64  
Чита (3022)38-34-83  
Якутск (4112)23-90-97  
Ярославль (4852)69-52-93

**Россия** +7(495)268-04-70

**Казахстан** +7(727)345-47-04

**Беларусь** +(375)257-127-884

**Узбекистан** +998(71)205-18-59

**Киргизия** +996(312)96-26-47

По вопросам продаж и поддержки обращайтесь:

эл.почта: [cie@nt-rt.ru](mailto:cie@nt-rt.ru) || сайт: <https://celli.nt-rt.ru/>