Кулеры TE, TE-MIX

Технические характеристики

По вопросам продаж и поддержки обращайтесь:

Алматы (727)345-47-04 Ангарск (3955)60-70-56 Архангельск (8182)63-90-72 Астрахань (8512)99-46-04 Барнаул (3852)73-04-60 Белгород (4722)40-23-64 Благовещенск (4162)22-76-07 Брянск (4832)59-03-52 Владивосток (423)249-28-31 Владикавказ (8672)28-90-48 Владимир (4922)49-43-18 Волгоград (844)278-03-48 Вологда (8172)26-41-59 Воронеж (473)204-51-73 Екатеринбург (343)384-55-89

Россия +7(495)268-04-70

Иваново (4932)77-34-06 Ижевск (3412)26-03-58 Иркутск (395)279-98-46 Казань (843)206-01-48 Калининград (4012)72-03-81 Калуга (4842)92-23-67 Кемерово (3842)65-04-62 Киров (8332)68-02-04 Коломна (4966)23-41-49 Кострома (4942)77-07-48 Краснодар (861)203-40-90 Красноярск (391)204-63-61 Курск (4712)77-13-04 Курган (3522)50-90-47 Липецк (4742)52-20-81

Казахстан +7(727)345-47-04

Магнитогорск (3519)55-03-13 Москва (495)268-04-70 Мурманск (8152)59-64-93 Набережные Челны (8552)20-53-41 Нижний Новгород (831)429-08-12 Ноябрьск (3496)41-32-12 Новосибирск (383)227-86-73 Омск (3812)21-46-40 Орел (4862)44-53-42 Оренбург (3532)37-68-04 Пенза (8412)22-31-16 Петрозаводск (8142)55-98-37 Псков (8112)59-10-37 Пермь (342)205-81-47

Беларусь +(375)257-127-884

Ростов-на-Дону (863)308-18-15 Рязань (4912)46-61-64 Самара (846)206-03-16 Санкт-Петербург (812)309-46-40 Саратов (845)249-38-78 Севастополь (8692)22-31-93 Саранск (8342)22-96-24 Симферополь (3652)67-13-56 Смоленск (4812)29-41-54 Сочи (862)225-72-31 Ставрополь (8652)20-65-13 Сургут (3462)77-98-35 Сыктывкар (8212)25-95-17 Тамбов (4752)50-40-97 Тверь (4822)63-31-35

Узбекистан +998(71)205-18-59

Тольятти (8482)63-91-07 Томск (3822)98-41-53 Тула (4872)33-79-87 Тюмень (3452)66-21-18 Ульяновск (8422)24-23-59 Улан-Удэ (3012)59-97-51 Уфа (347)229-48-12 Хабаровск (4212)92-98-04 Чебоксары (8352)28-53-07 Челябинск (351)202-03-61 Череповец (8202)49-02-64 Чита (3022)38-34-83 Якутск (4112)23-90-97 Ярославль (4852)69-52-93

Киргизия +996(312)96-26-47



Tornado Evolution

The Tornado Evolution range, offering various models primarily differentiated by capacity, features a blue Skin Plate body, mechanical thermostat, copper evaporator and ocpper-aluminium condenser.



KEY STRENGTHS



The Tornado Evolution range is equipped with ice bank technology, varying from 25 to 65 liters depending on the model, designed for fixed undercounter draught systems. With Tornado Evolution, it is possible to dispense up to 62 L/h at peak performance for the smallest model, and up to 155 L/h for the largest model, thanks to a refrigeration circuit with fast startup and quick recovery during high-demand periods.





Advanced Features

The creation of the ice bank from scratch is quick (3 hours), as is its reformation. The machine is equipped with a mechanical thermostat.



Serviceability

The bodywork of the Tornado Evolution can be opened on two sides by removing a single panel. Machine rollers are available to facilitate sliding it into position.



The external body is made of steel with a blue skin-plate coating, ensuring good resistance to splashes and spills in the installation area.



In the Tornado Evolution, the tank can be emptied through the drain pipe located at the front. As with all Celli refrigeration coolers, the Hi-ClO digital and eco-friendly sanitization system can be applied to sanitize product lines.







TORNADO EVOLUTION ______

Tornado Evolution 15

Type of beverages

Refrigerant gas

Finishing






R290 /R134a

Skin-Plate blu

Lines









		Vertical - 1/5 CV	Vertical - 1/4 CV
General data sheet			
Water basin (net)	L	14	14
Ice bank	kg	7	7
Compressor's nominal power	CV	1/5	1/4
Standard agitator pump	m	1 stage 5.8m	1 stage 5.8m
Performance & Consumption			
Performance - Cooling power	W	387	453
Performance - houry peak - ΔT20°C	L/h	44	49
Performance - daily average - ΔT20°C	L/h	17	21
Max power absorption	W	240	270
Average daily consumption - standby **	kWh		
Average daily consumption**	kWh		
Overall Height (with pump)*	ст	59	59
Length x Width	ст х ст	41 x 33	41 x 33
Net Empty Weight	kg	26	26
Coils - max number 15/20 m each***	п°	2	2
Coils - max number including 10 m coils**	п°	2	2
Available Versions			
Electric supply		220-240V AC 50 Hz	220-240V AC 50 Hz
Plug to choose		Schuko, I	Schuko, I
Options to chose			
Number of coils	п°	from 1 to 2	from 1 to 2
Coils inlet/outlet		basic (tube cut) / JG speedfit fitting [opt]	basic (tube cut) / JG speedfit fitting [opt]
Coils diameter	mm x mm	7x8	7x8
Thermostat option		electronic; depending on the item	electronic; depending on the item



Tornado Evolution 25

Type of beverages

Refrigerant gas

Finishing






R290 /R134a

Skin-Plate blu

Lines









		Vertical - 1/3 CV
General data sheet		
Water basin (net)	L	20
Ice bank	kg	10
Compressor's nominal power	CV	1/4
Standard agitator pump	m	1 stage 6.5 m
Performance & Consumption		
Performance - Cooling power	W	453
Performance - houry peak - ΔT20°C	L/h	62
Performance - daily average - ΔT20°C	L/h	22
Max power absorption	W	350
Average daily consumption - standby **	kWh	
Average daily consumption**	kWh	
Overall Height (with pump)*	cm	62
Length x Width	cm x cm	43 x 43
Net Empty Weight	kg	29
Coils - max number 15/20 m each***	n°	2
Coils - max number including 10 m coils**	n°	4
Available Versions		
Electric supply		220-240V AC 50 Hz
Plug to choose		Schuko, I
Options to chose		
Number of coils	n°	from 1 to 4
Coils inlet/outlet		basic (tube cut) / JG speedfit fitting [opt]
Coils diameter	mm x mm	7x8
Thermostat option		electronic; depending on the item



Each item number includes coils, pump, plugV

This is a all-comprehensive list fo all possibile features, that are already technically feasible. Not all the combinations of these features (not each configuration) is already present in stock and in the price list. Reference can be found in the Celli price list.

Tornado Evolution 35

Type of beverages

Refrigerant gas

Finishing






R290 /R134a

Skin-Plate blu

Lines









		Vertical - 1/3 CV	Vertical - 1/2 CV
General data sheet			
Water basin (net)	L	29	29
Ice bank	kg	14	14
Compressor's nominal power	CV	1/3	1/2
Standard agitator pump	m	1 stage from 5.8 to 8.0 m	1 stage from 5.8 to 8.0 m
Performance & Consumption			
Performance - Cooling power	W	571	905
Performance - houry peak - ΔT20°C	L/h	83	94
Performance - daily average - ΔT20°C	L/h	27	39
Max power absorption	W	370	570
Average daily consumption - standby **	kWh		
Average daily consumption**	kWh		
Overall Height (with pump)*	ст	71	71
Length x Width	ст х ст	47 x 42	47 x 42
Net Empty Weight	kg	36	36
Coils - max number 15/20 m each***	п°	3	3
Coils - max number including 10 m coils**	n°	4	4
Available Versions			
Electric supply		220-240V AC 50 Hz	220-240V AC 50 Hz
Plug to choose		Schuko, I	Schuko, I
Options to chose			
Number of coils	п°	from 1 to 4	from 1 to 4
Coils inlet/outlet		basic (tube cut) / JG speedfit fitting [opt]	basic (tube cut) / JG speedfit fitting [opt]
Coils diameter	mm x mm	7x8	7x8
Thermostat option		electronic; depending on the item	electronic; depending on the item



Each item number includes coils, pump, plugV

This is a all-comprehensive list fo all possibile features, that are already technically feasible. Not all the combinations of these features (not each configuration) is already present in stock and in the price list. Reference can be found in the Celli price list.

Tornado Evolution 50

Type of beverages

Refrigerant gas

Finishing







R290 /R134a



Lines









	Vertical - 1/2 CV	Vertical - 1/3 CV
_		
L	44	44
kg	21	21
CV	1/2	1/3
m	1 stage from 6.5 to 8.0 m	1 stage from 6.5 to 8.0 m
W	905	895
L/h	122	122
L/h	39	39
W	570	570
kWh		
kWh		
cm	74	74
cm x cm	54 x 49	54 x 49
kg	36	36
n°	40	40
n°	5	5
	220-240V AC 50 Hz	220-240V AC 50 Hz
	Schuko, I	Schuko, I
n°	from 1 to 5	from 1 to 5
	basic (tube cut) / JG speedfit fitting [opt]	basic (tube cut) / JG speedfit fitting [opt]
mm x mm	7x8	7x8
	electronic; depending on the item	electronic; depending on the item
	kg CV m W L/h L/h W kWh kWh cm cmxcm kg n° n°	L



Each item number includes coils, pump, plugV

This is a all-comprehensive list fo all possibile features, that are already technically feasible. Not all the combinations of these features (not each configuration) is already present in stock and in the price list. Reference can be found in the Celli price list.

TORNADO EVOLUTION _

Tornado Evolution 65

Type of beverages

Refrigerant gas

Finishing





R290 /R134a

Skin-Plate blu

Lines









		Vertical - 3/4 CV	Vertical - 5/8 CV	Vertical - 5/8 CV
General data sheet				
Water basin (net)	L	52	52	52
Ice bank	kg	25	25	25
Compressor's nominal power	CV	3/4	5/8	1/2
Standard agitator pump	m	1 stage from 6.5 to 8.0 m	1 stage from 6.5 to 8.0 m	1 stage from 6.5 to 8.0 m
Performance & Consumption				
Performance - Cooling power	W	1.287	1.392	1.169
Performance - houry peak - ΔT20°C	L/h	155	159	150
Performance - daily average - ΔT20°C	L/h	56	60	50
Max power absorption	W	710	640	570
Average daily consumption - standby **	kWh			
Average daily consumption**	kWh			
Overall Height (with pump)*	cm	77	77	77
Length x Width	cm x cm	59 x 54	59 x 54	59 x 54
Net Empty Weight	kg	52	52	52
Coils - max number 15/20 m each***	n°	5	5	5
Coils - max number including 10 m coils**	n°	6	6	6
Available Versions				
Electric supply		220-240V AC 50 Hz	220-240V AC 50 Hz	220-240V AC 50 Hz
Plug to choose		Schuko, I	Schuko, I	Schuko, I
Options to chose				
Number of coils	n°	from 1 to 6	from 1 to 6	from 1 to 6
Coils inlet/outlet		basic (tube cut) / JG speedfit fitting [opt]	basic (tube cut) / JG speedfit fitting [opt]	basic (tube cut) / JG speedfit fitting [opt]
Coils diameter	mm x mm	7x8	7x8	7x8
Thermostat option		electronic; depending on the item	electronic; depending on the item	electronic; depending on the item



Each item number includes coils, pump, plugV

This is a all-comprehensive list fo all possibile features, that are already technically feasible. Not all the combinations of these features (not each configuration) is already present in stock and in the price list. Reference can be found in the Celli price list.



Coolers

TE 15

Tornado Evolution 15 is a 15 liter refrigeration machine with ice bank technology, designed for fixed draught systems in undercounter application. It supports up to 2 lines of approximately 10 metres.

Features:

Type of dispensed beverage:





Number of ways/lines:

✓ from 1 to 2

Number of people:

30-40

Finish:



Strengths



Performance

- Tornado Evolution 15 can dispense 17 L/h in continuous service or 44 L/h of peak performance (with a temperature delta of 20 degrees between inlet and outlet)
- The machine is equipped with a quick-start refrigeration circuit, which guarantees reduced times for creating the ice bank in around 3 hours, with excellent recovery in moments of maximum effort



Serviceability

- Tornado Evolution 15 features a design that simplifies maintenance, with a single removable panel that provide opening on two sides for quick and complete access to internal components
- The machine is equipped with sliding rollers, which allow easy positioning and movement



Design & User Experience

- Tornado Evolution 15 is covered in blue skinplate material, resistant to splashes and spills, ensuring superior durability and always maintaining a clean and modern appearance
- The compact design integrates easily into undercounter spaces, maximizing the available space



Hygiene & Safety

- Tornado Evolution 15 allows you to empty the tank via the drain pipe located at the front
- The system is compatible with the digital and ecological Hi-ClO sanitization system

Models of the **Tornando Evolution** series



Tornado Evolution 15

Water Basin (L)	14
Ice Bank (kg)	7
Cooling Power (W)	387 - 453
Coils (n max)	2



Tornado Evolution 25

Water Basin (L)	20
Ice Bank (kg)	10
Cooling Power (W)	453
Coils (n max)	2



Water Basin (L)	29
Ice Bank (kg)	14
Cooling Power (W)	571 - 905

Coils (n max)



Tornado Evolution 50

Water Basin (L)	44
Ice Bank (kg)	21
Cooling Power (W)	895 - 905
Coils (n max)	5



Water Basin (L)	52
Ice Bank (kg)	25
Cooling Power (W)	1.169 - 1.392
Coils (n max)	5



Coolers

TE 25

Tornado Evolution 25 is a 25 liter refrigeration machine with ice bank technology, designed for fixed draught systems in undercounter application. It supports up to 4 lines, with the possibility of connecting 2 lines of 20 meters and additional lines of shorter length.

Features:

Type of dispensed beverage:



Reer



Number of ways/lines:



Number of people:



Finish:



Strengths



Performance

- Tornado Evolution 25 can dispense 22 L/h in continuous service or 65 L/h of peak performance (with a temperature delta of 20 degrees between inlet and outlet)
- The machine is equipped with a quick-start refrigeration circuit, which guarantees reduced times for creating the ice bank in around 3 hours, with excellent recovery in moments of maximum effort



Serviceability

- Tornado Evolution 25 features a design that simplifies maintenance, with a single removable panel that provide opening on two sides for quick and complete access to internal components
- The machine is equipped with sliding rollers, which allow easy positioning and movement



Design & User Experience

- Tornado Evolution 25 is covered in blue skinplate material, resistant to splashes and spills, ensuring superior durability and always maintaining a clean and modern appearance
- The compact design integrates easily into undercounter spaces, maximizing the available space



Hygiene & Safety

- Tornado Evolution 25 allows you to empty the tank via the drain pipe located at the front
- The system is compatible with the digital and ecological Hi-ClO sanitization system

Models of the **Tornando Evolution** series



Tornado Evolution 15

Water Basin (L)	14
Ice Bank (kg)	7
Cooling Power (W)	387 - 453
Coils (n max)	2



Tornado Evolution 25

Water Basin (L)	20
Ice Bank (kg)	10
Cooling Power (W)	453
Coils (n max)	2



Water Basin (L)	29
Ice Bank (kg)	14
Cooling Power (W)	571 - 905

Coils (n max)



Tornado Evolution 50

Water Basin (L)	44
Ice Bank (kg)	21
Cooling Power (W)	895 - 905
Coils (n max)	5



Water Basin (L)	52
Ice Bank (kg)	25
Cooling Power (W)	1.169 - 1.392
Coils (n max)	5



Coolers

TE 35

Tornado Evolution 35 is a 35 liter refrigeration machine with ice bank technology, designed for fixed draught systems in undercounter application. It supports up to 4 lines, with the possibility of connecting 3 lines of 20 meters and additional lines of shorter length.

Features:

Type of dispensed beverage:



Reer



Number of ways/lines:



Number of people:



Finish:



Strengths



Performance

- Tornado Evolution 35 can dispense 27 L/h in continuous service or 83 L/h of peak performance (with a temperature delta of 20 degrees between inlet and outlet)
- The machine is equipped with a quick-start refrigeration circuit, which guarantees reduced times for creating the ice bank in around 3 hours, with excellent recovery in moments of maximum effort



Serviceability

- Tornado Evolution 35 features a design that simplifies maintenance, with a single removable panel that provide opening on two sides for quick and complete access to internal components
- The machine is equipped with sliding rollers, which allow easy positioning and movement



Design & User Experience

- Tornado Evolution 35 is covered in blue skinplate material, resistant to splashes and spills, ensuring superior durability and always maintaining a clean and modern appearance
- The compact design integrates easily into undercounter spaces, maximizing the available space



Hygiene & Safety

- Tornado Evolution 35 allows you to empty the tank via the drain pipe located at the front
- The system is compatible with the digital and ecological Hi-ClO sanitization system

Models of the **Tornando Evolution** series



Tornado Evolution 15

Water Basin (L)	14
Ice Bank (kg)	7
Cooling Power (W)	387 - 453
Coils (n max)	2



Tornado Evolution 25

Water Basin (L)	20
Ice Bank (kg)	10
Cooling Power (W)	453
Coils (n max)	2



Water Basin (L)	29
Ice Bank (kg)	14
Cooling Power (W)	571 - 905

Coils (n max)



Tornado Evolution 50

Water Basin (L)	44
Ice Bank (kg)	21
Cooling Power (W)	895 - 905
Coils (n max)	5



Water Basin (L)	52
Ice Bank (kg)	25
Cooling Power (W)	1.169 - 1.392
Coils (n max)	5



Coolers

TE 50

Tornado Evolution 50 is a 50 liter refrigeration machine with ice bank technology, designed for fixed draught systems in undercounter application. It supports up to 5 lines, with the possibility of connecting 5 lines of 20 meters and additional lines of shorter length.

Features:

Type of dispensed beverage:



Bee



Number of ways/lines:



Number of people:



Finish:



Strengths



Performance

- Tornado Evolution 50 can dispense 39 L/h in continuous service or 122 L/h of peak performance (with a temperature delta of 20 degrees between inlet and outlet)
- The machine is equipped with a quick-start refrigeration circuit, which guarantees reduced times for creating the ice bank in around 3 hours, with excellent recovery in moments of maximum effort



Serviceability

- Tornado Evolution 50 features a design that simplifies maintenance, with a single removable panel that provide opening on two sides for quick and complete access to internal components
- The machine is equipped with sliding rollers, which allow easy positioning and movement



Design & User Experience

- Tornado Evolution 50 is covered in blue skinplate material, resistant to splashes and spills, ensuring superior durability and always maintaining a clean and modern appearance
- The compact design integrates easily into undercounter spaces, maximizing the available space



Hygiene & Safety

- Tornado Evolution 50 allows you to empty the tank via the drain pipe located at the front
- The system is compatible with the digital and ecological Hi-ClO sanitization system

Models of the **Tornando Evolution** series



Tornado Evolution 15

Water Basin (L)	14
Ice Bank (kg)	7
Cooling Power (W)	387 - 453
Coils (n max)	2



Tornado Evolution 25

Water Basin (L)	20
Ice Bank (kg)	10
Cooling Power (W)	453
Coils (n max)	2



Water Basin (L)	29
Ice Bank (kg)	14
Cooling Power (W)	571 - 905

Coils (n max)



Tornado Evolution 50

Water Basin (L)	44
Ice Bank (kg)	21
Cooling Power (W)	895 - 905
Coils (n max)	5



Water Basin (L)	52
Ice Bank (kg)	25
Cooling Power (W)	1.169 - 1.392
Coils (n max)	5



Coolers

TE 65

Tornado Evolution 65 is a 65 liter refrigeration machine with ice bank technology, designed for fixed draught systems in undercounter application. It supports up to 6 lines, with the possibility of connecting 5 lines of 20 meters and additional lines of shorter length.

Features:

Type of dispensed beverage:



Beei



Number of ways/lines:

⋖ from 1 to 6

Number of people:



Finish:



Strengths



Performance

- Tornado Evolution 65 can dispense 56 L/h in continuous service or 155 L/h of peak performance (with a temperature delta of 20 degrees between inlet and outlet)
- The machine is equipped with a quick-start refrigeration circuit, which guarantees reduced times for creating the ice bank in around 3 hours, with excellent recovery in moments of maximum effort



Serviceability

- Tornado Evolution 65 features a design that simplifies maintenance, with a single removable panel that provide opening on two sides for quick and complete access to internal components
- The machine is equipped with sliding rollers, which allow easy positioning and movement



Design & User Experience

- Tornado Evolution 65 is covered in blue skinplate material, resistant to splashes and spills, ensuring superior durability and always maintaining a clean and modern appearance
- The compact design integrates easily into undercounter spaces, maximizing the available space



Hygiene & Safety

- Tornado Evolution 65 allows you to empty the tank via the drain pipe located at the front
- The system is compatible with the digital and ecological Hi-ClO sanitization system

Models of the **Tornando Evolution** series



Tornado Evolution 15

Water Basin (L)	14
Ice Bank (kg)	7
Cooling Power (W)	387 - 453
Coils (n max)	2



Tornado Evolution 25

Water Basin (L)	20
Ice Bank (kg)	10
Cooling Power (W)	453
Coils (n max)	2



Water Basin (L)	29
Ice Bank (kg)	14
Cooling Power (W)	571 - 905

Coils (n max)



Tornado Evolution 50

Water Basin (L)	44
Ice Bank (kg)	21
Cooling Power (W)	895 - 905
Coils (n max)	5



Water Basin (L)	52
Ice Bank (kg)	25
Cooling Power (W)	1.169 - 1.392
Coils (n max)	5

TE-MIX

The various versions of Te-Mix deliver large quantities of cold, still or sparkling water and are therefore suitable for large scale users. The double coil ice bank makes dispensing faster and more efficient for the dispensing of cold sparkling water.



Types of water:







Suggested optionals

WATER BLOCK, NO SHOCK, filtration system,

PRV, PRV+, R-RIC+, R-RIC MAX 5,5, KIT INST

description		*	\odot	lt/h	continuously It	R290 code	R134a code	dimension (WxDxH)
TEM16-8LT	•	•	•	50	12	215597	300037	33,0x43,0x40,5
TEM16-15L CSSC- 1/5A- 3.8S	•	•	•	80	60	215591	084924	33,4x40,7x61,2
TEM16-25L CSSC- 1/4A- 7.0S	•	•	•	150	80	102889	084860	42,7x42,6x61,2
TEM16-50L CSSC- 1/2A- 6.5C	•	•	•	220	150	215594	085613	49,1x54,1x74,2
TEM16-65L CSSC- 3/4A- 6.5C	•	•	•	280	200	215595	073007	54,1x59,1x77,5





COMPLETE INSTALLATION WITH:



DRIPTRAY for the complete range go to page 130



TOWER for the complete range go to page 128



DRINK TOWER for the complete range go to page 68



WATERBAR for the complete range go to page 94



Coolers

TE-MIX8

TE-MIX 8 is a 50 liter refrigeration machine with ice bank technology, ideal for low/medium capacity restaurants or cafés. Designed for fixed dispensing systems applied under the counter or in remote corners of the room, it allows the dispensing of water at room temperature, cold or sparkling.

Features:

Type of dispensed beverage: Water
Number of ways/lines:
✓ from 1 to 2
Number of people:
⋖ 50-60
Types of water:
Ambient Natural cold Sparkling cold

Finish:



Strengths



Performance

- TE-MIX 8 can dispense up to 50 liters per hour of cold water, still and sparkling, or water at room temperature, with a capacity of 12 L/h in continuous service
- The ice bank with double coil in the ACWG versions makes the simultaneous dispensing of cold and sparkling water faster and more efficient



Advanced Features

 TE-MIX 8 supports the application of dechlorinator and purifier filters to improve the taste and smell of water



Design & User Experience

- Thanks to its compact and solid design, TE-MIX 8 can be installed either under the bar counter or away from the taps, ensuring practicality and flexibility in different installation and use conditions
- A wide choice of taps and fonts allow for product customization based on specific needs



Label & Certification

 TE-MIX 8 is tested and engineered in the Celli testing laboratories and complies with the technical regulations for a wide range of countries: EU, UK, APAC

Models of the **TE-MIX** series



TE-MIX 8

L/H continuous 50

Channel Horeca - Small Size

Water type Ambient, Sparkling, Natural cold



TE-MIX 15

L/H continuous 80

Channel Horeca - Big Size

Water type Ambient, Sparkling, Natural cold



TE-MIX 25

L/H continuous 150

Channel Horeca - Big Size

Water type Ambient, Sparkling, Natural cold



TE-MIX 50

L/H continuous 220

Channel Horeca - Big Size

Water type

Ambient, Sparkling, Natural cold



TE-MIX 65

L/H continuous 280

Channel Horeca - Big Size

Water type Ambient, Sparkling, Natural cold



Coolers

TE-MIX 15

TE-MIX 15 is an 80-litre refrigeration machine with ice bank technology, ideal for medium-capacity restaurants or cafés. Designed for fixed dispensing systems applied under the counter or in remote corners of the room, it allows the dispensing of water at room temperature, cold or sparkling.

Features:

Тур	e of dispensed	beverage
	Water	

Number of ways/lines:

✓ from 1 to 2

Number of people:

✓ 100-125 **✓** 125-150

Types of water:



Finish:



Strengths



Performance

- TE-MIX 15 can dispense up to 80 liters per hour of cold water, still and sparkling, or water at room temperature, with a capacity of 60 L/h in continuous service
- The ice bank with double coil in the ACWG versions makes the simultaneous dispensing of cold and sparkling water faster and more efficient



Advanced Features

 TE-MIX 15 supports the application of dechlorinator and purifier filters to improve the taste and smell of water



Design & User Experience

- Thanks to its compact and solid design, TE-MIX 15 can be installed either under the bar counter or away from the taps, ensuring practicality and flexibility in different installation and use conditions
- A wide choice of taps and fonts allow for product customization based on specific needs



Label & Certification

 TE-MIX 15 is tested and engineered in the Celli testing laboratories and complies with the technical regulations for a wide range of countries: EU, UK, APAC



TE-MIX 8

L/H continuous 50

Channel Horeca - Small Size

Water type Ambient, Sparkling, Natural cold



TE-MIX 15

L/H continuous 80

Channel Horeca - Big Size

Water type Ambient, Sparkling, Natural cold



TE-MIX 25

L/H continuous 150

Channel Horeca - Big Size

Water type Ambient, Sparkling, Natural cold



TE-MIX 50

Water type

Ambient, Sparkling, Natural cold



TE-MIX 65

L/H continuous 280

Channel Horeca - Big Size



Coolers

TE-MIX 25

TE-MIX 25 is a 150 liter refrigeration machine with ice bank technology, ideal for medium/high capacity restaurants or cafes. Designed for fixed dispensing systems applied under the counter or in remote corners of the room, it allows the dispensing of water at room temperature, cold or sparkling.

Features:

Type of dispensed beverage:
Water
Number of ways/lines:
✓ from 1 to 2
Number of people:
✓ 150-200
Types of water:
Ambient Natural cold Sparkling cold

Finish:



Strengths



Performance

- TE-MIX 25 can dispense up to 150 liters per hour of cold water, still and sparkling, or water at room temperature, with a capacity of 80 L/h in continuous service
- The ice bank with double coil in the ACWG versions makes the simultaneous dispensing of cold and sparkling water faster and more efficient



Advanced Features

 TE-MIX 25 supports the application of dechlorinator and purifier filters to improve the taste and smell of water



Design & User Experience

- Thanks to its compact and solid design, TE-MIX 25 can be installed either under the bar counter or away from the taps, ensuring practicality and flexibility in different installation and use conditions
- A wide choice of taps and fonts allow for product customization based on specific needs



Label & Certification

 TE-MIX 25 is tested and engineered in the Celli testing laboratories and complies with the technical regulations for a wide range of countries: EU, UK, APAC



TE-MIX 8

L/H continuous 50

Channel Horeca - Small Size

Water type Ambient, Sparkling, Natural cold



TE-MIX 15

L/H continuous 80

Channel Horeca - Big Size

Water type Ambient, Sparkling, Natural cold



TE-MIX 25

L/H continuous 150

Channel Horeca - Big Size

Water type Ambient, Sparkling, Natural cold



TE-MIX 50

Water type

Ambient, Sparkling, Natural cold



TE-MIX 65

L/H continuous 280

Channel Horeca - Big Size



Coolers

TE-MIX 50

TE-MIX 50 is a 220 liter refrigeration machine with ice bank technology, ideal for high capacity restaurants or cafes. Designed for fixed dispensing systems applied under the counter or in remote corners of the room, it allows the dispensing of water at room temperature, cold or sparkling.

Features:

Type of dispensed beverage:
Water
Number of ways/lines:
from 1 to 2

Number of people:

⋖ >250

Types of water:



Finish:



Strengths



Performance

- TE-MIX 50 can dispense up to 220 liters per hour of cold water, still and sparkling, or water at room temperature, with a capacity of 150 L/h in continuous service
- The ice bank with double coil in the ACWG versions makes the simultaneous dispensing of cold and sparkling water faster and more efficient



Advanced Features

 TE-MIX 50 supports the application of dechlorinator and purifier filters to improve the taste and smell of water



Design & User Experience

- Thanks to its compact and solid design, TE-MIX 50 can be installed either under the bar counter or away from the taps, ensuring practicality and flexibility in different installation and use conditions
- A wide choice of taps and fonts allow for product customization based on specific needs



Label & Certification

 TE-MIX 50 is tested and engineered in the Celli testing laboratories and complies with the technical regulations for a wide range of countries: EU, UK, APAC



TE-MIX 8

L/H continuous 50

Channel Horeca - Small Size

Water type Ambient, Sparkling, Natural cold



TE-MIX 15

L/H continuous 80

Channel Horeca - Big Size

Water type Ambient, Sparkling, Natural cold



TE-MIX 25

L/H continuous 150

Channel Horeca - Big Size

Water type Ambient, Sparkling, Natural cold



TE-MIX 50

Water type

Ambient, Sparkling, Natural cold



TE-MIX 65

L/H continuous 280

Channel Horeca - Big Size



Coolers

TE-MIX 65

TE-MIX 65 is a 280 liter refrigeration machine with ice bank technology, ideal for high capacity restaurants or cafes. Designed for fixed dispensing systems applied under the counter or in remote corners of the room, it allows the dispensing of water at room temperature, cold or sparkling.

Features:

Type of dispensed beverage:
Water
Number of ways/lines:
✓ from 1 to 2
Number of people:

Types of water:

⋖ >250



Finish:



Strengths



Performance

- TE-MIX 65 can dispense up to 280 liters per hour of cold water, still and sparkling, or water at room temperature, with a capacity of 200 L/h in continuous service
- The ice bank with double coil in the ACWG versions makes the simultaneous dispensing of cold and sparkling water faster and more efficient



Advanced Features

 TE-MIX 65 supports the application of dechlorinator and purifier filters to improve the taste and smell of water



Design & User Experience

- Thanks to its compact and solid design, TE-MIX 65 can be installed either under the bar counter or away from the taps, ensuring practicality and flexibility in different installation and use conditions
- A wide choice of taps and fonts allow for product customization based on specific needs



Label & Certification

 TE-MIX 65 is tested and engineered in the Celli testing laboratories and complies with the technical regulations for a wide range of countries: EU, UK, APAC



TE-MIX 8

L/H continuous 50

Channel Horeca - Small Size

Water type Ambient, Sparkling, Natural cold



TE-MIX 15

L/H continuous 80

Channel Horeca - Big Size

Water type Ambient, Sparkling, Natural cold



TE-MIX 25

L/H continuous 150

Channel Horeca - Big Size

Water type Ambient, Sparkling, Natural cold



TE-MIX 50

Water type

Ambient, Sparkling, Natural cold



TE-MIX 65

L/H continuous 280

Channel Horeca - Big Size

По вопросам продаж и поддержки обращайтесь:

Алматы (727)345-47-04 Ангарск (3955)60-70-56 Архангельск (8182)63-90-72 Астрахань (8512)99-46-04 Барнаул (3852)73-04-60 Белгород (4722)40-23-64 Благовещенск (4162)22-76-07 Брянск (4832)59-03-52 Владивосток (423)249-28-31 Владикавказ (8672)28-90-48 Владимир (4922)49-43-18 Волгоград (844)278-03-48 Вологда (8172)26-41-59 Воронеж (473)204-51-73 Екатеринбург (343)384-55-89

Россия +7(495)268-04-70

Иваново (4932)77-34-06 Ижевск (3412)26-03-58 Иркутск (395)279-98-46 Казань (843)206-01-48 Калининград (4012)72-03-81 Калуга (4842)92-23-67 Кемерово (3842)65-04-62 Киров (8332)68-02-04 Коломна (4966)23-41-49 Кострома (4942)77-07-48 Краснодар (861)203-40-90 Красноярск (391)204-63-61 Курск (4712)77-13-04 Курган (3522)50-90-47 Липецк (4742)52-20-81

Казахстан +7(727)345-47-04 Беларусь +

Магнитогорск (3519)55-03-13 Москва (495)268-04-70 Мурманск (8152)59-64-93 Набережные Челны (8552)20-53-41 Нижний Новгород (831)429-08-12 Новокузнецк (3843)20-46-81 Ноябрьск (3496)41-32-12 Новосибирск (383)227-86-73 Омск (3812)21-46-40 Орел (4862)44-53-42 Оренбург (3532)37-68-04 Пенза (8412)22-31-16 Петрозаводск (8142)55-98-37 Псков (8112)59-10-37 Пермь (342)205-81-47

Беларусь +(375)257-127-884

Ростов-на-Дону (863)308-18-15 Рязань (4912)46-61-64 Самара (846)206-03-16 Санкт-Петербург (812)309-46-40 Саратов (845)249-38-78 Севастополь (8692)22-31-93 Саранск (8342)22-96-24 Симферополь (3652)67-13-56 Смоленск (4812)29-41-54 Сочи (862)225-72-31 Ставрополь (8652)20-65-13 Сургут (3462)77-98-35 Сыктывкар (8212)25-95-17 Тамбов (4752)50-40-97 Тверь (4822)63-31-35

Узбекистан +998(71)205-18-59

Тольятти (8482)63-91-07 Томск (3822)98-41-53 Тула (4872)33-79-87 Тюмень (3452)66-21-18 Ульяновск (8422)24-23-59 Улан-Удэ (3012)59-97-51 Уфа (347)229-48-12 Хабаровск (4212)92-98-04 Чебоксары (8352)28-53-07 Челябинск (351)202-03-61 Череповец (8202)49-02-64 Чита (3022)38-34-83 Якутск (4112)23-90-97 Ярославль (4852)69-52-93

Киргизия +996(312)96-26-47